



UNICORN COMPUTER CORP.

ADD : 3FL-4., No. 130, Chien-Kung Rd., Chung-Ho City, Taipei Hsien, Taiwan 235

TEL : 886-2-2223-6699 • 2223-6655 FAX : 886-2-2222-1269

Web Site : www.unicorn-computer.com.tw

E-Mail : sales@unicorn-computer.com.tw • support@unicorn-computer.com.tw

U-1000

Specifications

Dimensions:

379mm (D) x 300mm (W) x 76mm (H)
14.9" (D) x 11.8" (W) x 3.0" (H)

Weight:

Case only: 5.0Kg
With Packaging: 6.0Kg

Expansions:

3 slots available to match with riser cards:
GE-11: 1 x PCI, 1 x PCI / ISA
U-2003: 1 x PCI, 1 x PCI / ISA, 1 x ISA
U-2005: 2 x PCI, 1 x ISA
JEI-010: 3 x ISA

Disk Drive Capacity:

HDD: One 3.5" standard size HDD
FDD: One 3.5" 1.44MB standard FDD,
or slim type FDD +CD-ROM
CD-ROM: One slim type CD-ROM

Paint Color:

Black (standard) or Beige (optional)

Power Supply:

Output Rating: ATX 136W (max.)
Output Voltage: +3.3V @ 4A
+5V @ 18A
+12V @ 2.1A
-12V @ 0.3A
+5Vsb @ 0.8A
Input Voltage: 100 / 220VAC adjustable
Input Frequency: 47 ~ 63 Hz
MTBF: 100,000Hrs

Cooling Fan:

One 6cm / 3600RPM / 15.2CFM case cooling fan
One optional 4cm / 7500RPM / 7.3CFM cooling fan

Controls:

Power On/Off switch

LED Indicator:

Power On/Off indicator
HDD Activity Indicator

EMC:

FCC, CE Compliant

Environment:

Operating Temperature: 0°C ~ 60°C
Storage Temperature: -20°C ~ 70°C
Relative Humidity: 10% ~ 90%

Form Factor:

LPX Format system boards
PC/AT Format system boards

Available *Unicorn* System Boards:

LPX Format: ENDAT-5701/3701/3702/3601M/3601T
PC/AT Format: ENDAT-5901/3902

Packaging Information:

2 in 1 carton packaging
Internal carton: 38cm(L) x 18cm(W) x 48.5cm(H)
External carton: 41.5cm (L) x 37cm(W) x 57cm(H)

Ordering Information:

Option:

U-RJ02 Second LAN kit for ENDAT-3601M/T systems
2nd FAN 4cm FAN (KDE1204PFB2-8)
FA-USB USB + Audio Kit for U-1000

LPX rear window:

4 x 9-pin D-Sub COM ports
1 x 25-pin D-Sub LPT port
1 x 15-pin D-Sub VGA port
1 x KB/Mouse port
1 x RJ45 LAN Jack port
3 x bracket openings



PC/AT rear window:

3 x 9-pin D-Sub COM ports
2 x 25-pin D-Sub LPT ports
1 x 15-pin D-Sub VGA port
1 x KB/Mouse port
1 x RJ45 LAN Jack port
3 x bracket openings



PC/AT 3ISA rear window:

3 x 9-pin D-Sub COM ports
1 x 25-pin D-Sub LPT port
1 x 15-pin D-Sub VGA port
1 x KB/Mouse port
1 x RJ45 LAN Jack port
3 x bracket openings

